



PROJECT	DATE
TYPE	QTY

IP 68 UNDERWATER LED STAINLESS STEEL LIGHT FIXTURE

UX-50-1023
 Threaded Flange for 1.5" F.I.P.

UX-50-1023
DESCRIPTION:

The UX-50 Stainless Steel LED Underwater Fixture has a variety of uses. With an IP68 rating this line is designed and engineered for outdoor and underwater use. This compact fixture is a powerhouse with a range of 45 to 90+ lumens per Watt.

A rugged 316 stainless steel fixture with a 10mm thick tempered glass lens covers a powerful 10W CREE high lumen output, high efficiency LED. Available in warm white, neutral white, cool white and RGB+W configurations.

The UX-50-P is a PVC pipe mount for grotto and landscape lighting.

The UX-50-T is a tripod mount with swivel U-bracket perfect for water features, fountains and wet architectural lighting.

The UX-50-1023 fits SP1023 and 1.5" F.I.P. for pools and spas.

FEATURES:

- No Visible LED Spots
- IP68
- 316 Stainless Steel
- 10mm tempered glass lens
- 10W CREE LED
- 4 LED color option

SPECIFICATIONS



Material	316 Stainless Steel
Cover	Tempered Glass (T=10mm)
IP Rating	IP68
Typical Power Consumption	10W
Input Voltage	12VDC Constant Current 350mA/700mA
Control	DMX512 / ON/ OFF
DMX Channel	4CHS (RGBW) @ DMX512 Control
Light Source	CREE
LED Chip Range	XP-E/XM-L High Lumen Output, High Efficacy
LED Quantity	1PCS
Color/CCT	3000K / 4000K / 6500K / RGBW
CRI	Ra ≥ 80
Lifespan	50,000 hrs.
Beam Angle	10°, 25°, 38°
Product Size	Ø2" x 1.5" x 1.9" h Ø50mm 39mm 49mm
Weight	0.9LBS / 0.41KG
Environment Parameter	Work Temperature -25°~45°
Storage Humidity	0~90°

* 12VDC Requires Constant Current Driver

PHOTOMETRICS

LED	TYPICAL LIGHT EFFICIENCY
3000K	>55LM/W
4000K	>65LM/W
6000K	>90LM/W
RGB	>45LM/W


UX-50-T
 Tripod Mount

UX-50-P
 PVC Pipe Mount Fixture

UX-50-T
UX-50-P
ORDERING

MODEL	LED	BEAM ANGLE	CORD LENGTH
<input type="text"/>	- <input type="text"/>	- <input type="text"/>	- <input type="text"/>

UX-50-1023 - With Threaded Flange for 1.5" F.I.P

WW - 3000K
NW - 4000K
CW - 6500K

10 - 10°
25 - 25°
38 - 38°

15 - 15'
25 - 25'
50 - 50'
75 - 75'
100 - 100'

UX-50-T - Tripod Mount
UX-50-P - PVC Pipe Mount

RGB+W - Red/Green /Blue/White

ACCESSORIES

- DMX4** - 4 Channel DMX512 Decoder for RGB+W
- DE3** - STICK-DE3 DMX Wall Controller
- RS232** - Advanced RS232 Serial Controller
- EPICWIFI** - WiFi for Advanced RS232 Serial Cont.
- PS18CC** - 18W Constant Current Power Supply
- 1023W** - White Fitting for Pool Light
- 1023B** - Black Fitting for Pool Light

IMPACT LIGHTING