



Specifier's Reference

Project

# Туре

# **IMP-8000 RGB INDOOR LED ILLUMINATOR**

#### APPLICATION

The IMP-8000 DIS-4 Series LED Light Source is a 4-channel DMX illuminator. 3 Channels for RGB and 1 Channel for Animation Motor (5th channel for amber or white optional) . This light source can be used as a standalone or can be programmable using DMX 512, RS232 SERIAL, RF and Simple Dimmer Controller.

# HIGH CONTROL RESOLUTION

The IMP-8000 DIS Series LED Light Source supports a 16-bit control resolution per output channel for accurate dimming and fine color mixing.

#### LOW EMI

Slow-rate controlled dimming and shielded conductors keep the driver's EMI emissions at a very low level.

# ANIMATION

IMP-8000 DIS Series LED Light Source has a 10rpm (top speed) DC motor than can be speed controlled via DMX with an attached sparkle wheel.

# ROBUST THERMAL MANAGEMENT

The IMP's Sync® module creates turbulent, pulsated air-jets that can be directed precisely to locations where thermal management is needed. The vortex-dominated SynJet flow enhances small-scale mixing near the heated surfaces to yield higher effective heat transfer at low-volume flow rates compared to conventional air movers. The SynJet flow is created using a patented actuator technology and proprietary fluidic packaging expertise.

# FEATURES

- 2700 lumens output brightest in the industry
- Thermal sensor protection for longer LED lifespan

#### ADVANTAGES

- Accurate, smooth dimming and high-res colour mixing
- · Drive, control and thermal protection per fixture
- Easy network

# SPECIFICATION

| PARAMETER                        | MAX RATING     |  |
|----------------------------------|----------------|--|
| Input voltage to<br>power supply | 100-240 VAC    |  |
| Input voltage to<br>light source | 24V            |  |
| Amps                             | 4 Amps         |  |
| Wattage                          | 100 W Max      |  |
| Power supply                     | 24V DC Class 2 |  |
| Hz                               | 50/60          |  |
| Fiber capacity                   | 1000           |  |
| Operating temperature            | -10°C to 80° C |  |
| Weight                           | 7 lbs          |  |
| Outdoor rating                   | IP67           |  |
| Housing                          | Aluminum       |  |





#### ORDERING INFORMATION

|           | COLOR   | DEVICE               | SPARKLE               | STANDARD PLUGIN  | CABLE LENGTH                               |            |
|-----------|---|----------------------|-----------------------|--|--|------------|
| IMP-8000- | PURE WHITE<br>WARM WHITE<br>MIX RGB<br>MIXED RGBA<br>MIXED RGBW | PW WW MX<br>MA<br>MW | NO SPARKLE<br>SPARKLE | DMX<br>RF<br>SIMPLE CONTROL DIMMER (WHITE ONLY)<br>RS23S | 5 FT<br>25 FT<br>75 FT<br>100 FT<br>CUSTOM | PRINT SEND |



Comments or Special Instructions





